

Version 1.4 Revision Date 2016-05-26

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Jet RF (AMS 2629B Type 1)

Material : 1102078, 1024360, 1024363, 1024362, 1024361, 1105002

Use : Reference Fluid

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview

Danger

Form: Liquid Physical state: Liquid Color: Colorless Odor: gasoline-like

OSHA Hazards : Flammable Liquid, Moderate skin irritant, Reproductive hazard,

Aspiration hazard, Target Organ Effects

Classification

: Flammable liquids, Category 2

SDS Number:100000014265 1/18

Version 1.4 Revision Date 2016-05-26

Skin irritation, Category 2

Reproductive toxicity, Category 2

Specific target organ systemic toxicity - single exposure,

Category 3, Central nervous system

Specific target organ systemic toxicity - repeated exposure,

Category 2, Auditory organs Aspiration hazard, Category 1

Labeling

Symbol(s) :







Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child. H373: May cause damage to organs (Auditory organs) through

prolonged or repeated exposure.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been

read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapor/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

SDS Number:100000014265

Version 1.4 Revision Date 2016-05-26

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms : Jet RF (AMS 2629B Type 1)

Molecular formula : Mixture

Component	CAS-No.	Weight %	
Cyclohexane	110-82-7	30 - 60	
2,2,4-Trimethylpentane (Isooctane)	540-84-1	30 - 60	
Toluene	108-88-3	25 - 60	
tert-Butyl Disulfide	110-06-5	1 - 5	

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious

place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

SDS Number:100000014265 3/18

Version 1.4 Revision Date 2016-05-26

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a

physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

-17 °C (1 °F) Flash point

Autoignition temperature : No data available

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

> must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Hazardous decomposition

products

: Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

> ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

SDS Number: 100000014265 4/18

Version 1.4 Revision Date 2016-05-26

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage

Handling

Advice on safe handling Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

> exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with

local and national regulations.

Advice on protection against fire and explosion Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Ingredients	Basis	Value	Control parameters	Note
Cyclohexane	ACGIH	TWA	100 ppm,	CNS impair,
	OSHA Z-1	TWA	300 ppm, 1,050 mg/m3	(b),
	OSHA Z-1-A	TWA	300 ppm, 1,050 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	URT irr,
	ACGIH	TWA	300 ppm,	URT irr,
Toluene	ACGIH	TWA	20 ppm,	visual impair, female repro, pregnancy loss, BEI, A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	

The value in mg/m3 is approximate.

Not classifiable as a human carcinogen

BEI Substances for which there is a Biological Exposure Index or Indices (see BEI® section)

Central Nervous System impairment CNS impair

female repro Female reproductive pregnancy loss

Pregnancy loss

URT irr Upper Respiratory Tract irritation

visual impair Visual impairment

Hazardous components without workplace control parameters

SDS Number: 100000014265 5/18

Jet RF (AMS 2629B Type 1)

Version 1.4 Revision Date 2016-05-26

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Cyclohexane	110-82-7	Immediately Dangerous to Life or Health Concentration Value 1300 ppm	1995-03-01
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 ppm	1995-03-01

Biological exposure indices

US

Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01

Engineering measures

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection

Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may

SDS Number:100000014265 6/18

Version 1.4 Revision Date 2016-05-26

occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place. Wear as appropriate:. Flame retardant antistatic protective

clothing. Workers should wear antistatic footwear. Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : Liquid
Physical state : Liquid
Color : Colorless
Odor : gasoline-like

Safety data

Flash point : -17 °C (1 °F)

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

Autoignition temperature : No data available

SDS Number:100000014265 7/18

Version 1.4 Revision Date 2016-05-26

Molecular formula : Mixture

Molecular weight : Not applicable

pH : No data available

Freezing point : No data available

Pour point No data available

Boiling point/boiling range : 82 - 138 °C (180 - 280 °F)

Vapor pressure : 2.00 PSI

at 38 °C (100 °F)

Relative density : 0.77

at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : No data available

Relative vapor density : 1

(Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

No decomposition if stored and applied as directed.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition

products

: Hydrocarbons Carbon oxides

Other data : No decomposition if stored and applied as directed.

SDS Number:100000014265 8/18

Jet RF (AMS 2629B Type 1)

Version 1.4 Revision Date 2016-05-26

SECTION 11: Toxicological information

Jet RF (AMS 2629B Type 1)

Acute oral toxicity : LD50 Oral: > 5,000 mg/kg

Species: Rat

Method: Acute toxicity estimate

Jet RF (AMS 2629B Type 1)

Acute inhalation toxicity : LC50: > 20 mg/l

Exposure time: 4 h Species: Rat

Test atmosphere: vapor Method: Acute toxicity estimate

Acute toxicity estimate: 80.13 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Jet RF (AMS 2629B Type 1)

Acute dermal toxicity : LD50 Dermal: > 5,000 mg/kg

Species: Rabbit

Method: Acute toxicity estimate

Jet RF (AMS 2629B Type 1)

Skin irritation : May cause skin irritation in susceptible persons.

Jet RF (AMS 2629B Type 1)

Eye irritation : May cause irreversible eye damage.

Jet RF (AMS 2629B Type 1)

Sensitization : Did not cause sensitization on laboratory animals. Information

refers to the main ingredient.

Repeated dose toxicity

Cyclohexane : Species: Rat

Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm

Exposure time: 90 day

Number of exposures: 6 h/d, 5 d/wk

NOEL: 2000 ppm

SDS Number:100000014265 9/18

Version 1.4 Revision Date 2016-05-26

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 500, 2,000, 7000 ppm Exposure time: 13-14 wk

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 7000 ppm

Species: Mouse, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm Exposure time: 13-14 wk

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 2000 ppm Target Organs: Blood

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 668, 2220, 6646 ppm Exposure time: 13 weeks

Number of exposures: 6 hr/day 5 d/wk

NOEL: 8.117 mg/l 2220 ppm Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm

Exposure time: 15 wk

Number of exposures: 6.5 h/d, 5 d/wk

NOEL: 625 ppm

Species: Mouse

Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm

Exposure time: 14 wk

Number of exposures: 6.5 h/d, 5 d/wk

NOEL: 100 ppm

Carcinogenicity

Toluene : Species: Rat

Dose: 0, 600, 1200 ppm Exposure time: 2 yrs

Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity

Species: Mouse Dose: 0, 600, 1200 ppm Exposure time: 2 yrs

Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity

Reproductive toxicity

Cyclohexane : Species: Rat

SDS Number:100000014265 10/18

Version 1.4 Revision Date 2016-05-26

> Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm Number of exposures: 6 hr/d, 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 500 ppm NOAEL F1: 7000 ppm NOAEL F2: 7000 ppm

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat

Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 3000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

> Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm

Test period: 95 d

NOAEL Parent: 2000 ppm

Developmental Toxicity

Cyclohexane : Species: Rat

> Application Route: Inhalation Dose: 0, 500, 2,000, 7,000 PPM Number of exposures: 6 hr/d

Test period: GD 6-15

Method: OECD Guideline 414 NOAEL Teratogenicity: 7,000 ppm NOAEL Maternal: 500 ppm

Species: Rabbit

Application Route: Inhalation Dose: 0, 500, 2,000, 7,000 PPM Number of exposures: 6 hr/d

Test period: GD 6-18

Method: OECD Guideline 414 NOAEL Teratogenicity: 7,000 ppm

NOAEL Maternal: 500 ppm

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat

Application Route: Inhalation Dose: 0, 400, 1200 ppm Number of exposures: 6h/d Test period: GD6-15

NOAEL Teratogenicity: 1200 ppm NOAEL Maternal: 1200 ppm

Information given is based on data obtained from similar

substances.

SDS Number:100000014265

11/18

Version 1.4 Revision Date 2016-05-26

Species: Rat

Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6h/d Test period: GD6-15

Method: OECD Guideline 414 NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm

Test period: 95 d

NOAEL Teratogenicity: 400-750 ppm

Jet RF (AMS 2629B Type 1)

Aspiration toxicity

May be fatal if swallowed and enters airways.

Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity

hazard.

CMR effects

Cyclohexane : Carcinogenicity: Not classifiable as a human carcinogen.

Mutagenicity: Did not show mutagenic effects in animal

experiments.

Teratogenicity: Did not show teratogenic effects in animal

experiments.

Reproductive toxicity: No toxicity to reproduction

2,2,4-Trimethylpentane

(Isooctane)

Mutagenicity: Tests on bacterial or mammalian cell cultures

did not show mutagenic effects.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

Toluene Carcinogenicity: Not classifiable as a human carcinogen.

Mutagenicity: Animal testing did not show any mutagenic

effects.

Teratogenicity: Some evidence of adverse effects on

development, based on animal experiments.

Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on

animal experiments.

Jet RF (AMS 2629B Type 1)

Further information

: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

SECTION 12: Ecological information

Toxicity to fish

SDS Number:100000014265 12/18

Version 1.4 Revision Date 2016-05-26

Cyclohexane : LC50: 4.53 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 203

2,2,4-Trimethylpentane

(Isooctane)

LC50: 0.11 mg/l Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

substances.

Toluene LC50: 18 - 36 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Cyclohexane : EC50: 0.9 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

2,2,4-Trimethylpentane

(Isooctane)

EC50: 0.4 mg/l Exposure time: 48 h

Species: Daphnia magna (Water flea)

static test Information given is based on data obtained from

similar substances.

Toluene EC50: 3.78 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Toxicity to algae

Cyclohexane : EbC50: 3.4 mg/l

Exposure time: 72 h

Species: Selenastrum capricornutum (algae)

NOEC: 0.925 mg/l Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (microalgae)

Method: OECD Test Guideline 201

2,2,4-Trimethylpentane

(Isooctane)

EL50: 2.943 mg/l Exposure time: 72 h

Method: QSAR modeled data

Toluene EC50: 134 mg/l

Exposure time: 72 h

Species: Chlamydomonas angulosa (Green algae)

M-Factor

cyclohexane : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

SDS Number:100000014265 13/18

Version 1.4 Revision Date 2016-05-26

2,2,4-Trimethylpentane

(Isooctane)

: NOEC: 0.17 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Elimination information (persistence and degradability)

Bioaccumulation

Cyclohexane : Bioconcentration factor (BCF): 167

This material is not expected to bioaccumulate.

Biodegradability : This material is not expected to be readily biodegradable.

Ecotoxicology Assessment

Acute aquatic toxicity

Cyclohexane : Very toxic to aquatic life.

2,2,4-Trimethylpentane

(Isooctane)

: Very toxic to aquatic life.

Toluene : Toxic to aquatic life.

tert-Butyl Disulfide : Toxic to aquatic life.

Chronic aquatic toxicity

Cyclohexane : Very toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane

(Isooctane) Toluene : Very toxic to aquatic life with long lasting effects.

: Harmful to aquatic life with long lasting effects.

tert-Butyl Disulfide : Toxic to aquatic life with long lasting effects.

Results of PBT assessment

Cyclohexane

: Non-classified PBT substance, Non-classified vPvB substance

2,2,4-Trimethylpentane

(Isooctane)

: Non-classified PBT substance, Non-classified vPvB substance

Toluene : Non-classified vPvB substance, Non-classified PBT substance

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life

with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SDS Number:100000014265 14/18

Jet RF (AMS 2629B Type 1)

Version 1.4 Revision Date 2016-05-26

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-17 °C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SDS Number:100000014265 15/18

Jet RF (AMS 2629B Type 1)

Version 1.4 Revision Date 2016-05-26

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Fire Hazard

> Acute Health Hazard Chronic Health Hazard

CERCLA Reportable

Quantity

: 2950 lbs

Cyclohexane

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SARA 313 Ingredients : The following components are subject to reporting levels

established by SARA Title III, Section 313:

: Cyclohexane - 110-82-7 Toluene - 108-88-3

Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

: 2.2.4-Trimethylpentane (Isooctane) - 540-84-1

Toluene - 108-88-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

> Cyclohexane - 110-82-7 Toluene - 108-88-3

US State Regulations

SDS Number:100000014265 16/18

Version 1.4 Revision Date 2016-05-26

Pennsylvania Right To Know

: Cyclohexane - 110-82-7

2,2,4-Trimethylpentane (Isooctane) - 540-84-1

Toluene - 108-88-3

New Jersey Right To Know

: Cyclohexane - 110-82-7

2,2,4-Trimethylpentane (Isooctane) - 540-84-1

Toluene - 108-88-3

tert-Butyl Disulfide - 110-06-5

California Prop. 65

Ingredients

: WARNING: This product contains a chemical known in the

State of California to cause birth defects or other reproductive

harm

Notification status

Europe REACH : On the inventory, or in compliance with the inventory

United States of America TSCA : On TSCA Inventory

Canada NDSL : This product contains one or several components listed

in the Canadian NDSL.


Australia AICS : On the inventory, or in compliance with the inventory New Zealand NZIoC : On the inventory, or in compliance with the inventory Japan ENCS : On the inventory, or in compliance with the inventory Korea KECI : On the inventory, or in compliance with the inventory Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : Not in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



Further information

Legacy SDS Number : 432570

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

SDS Number:100000014265 17/18

Version 1.4 Revision Date 2016-05-26

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

18/18