

n-Heptane Primary Reference Fuel (PRF)

Version 1.8

Revision Date 2016-01-21

SECTION 1: Identification of the	substance/mixture and of the company/undertaking
Product information	
Product Name Material	 n-Heptane Primary Reference Fuel (PRF) 1084146, 1021846, 1021847, 1021848, 1021849, 1021850, 1031134
Company	 Chevron Phillips Chemical Company LP Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:	
EUROPE: BIG +32.14.584	nal)
SECTION 2: Hazards identification	on
	or mixture accordance with the hazard communication standard 29 CFR ntain all the information as required by the standard.
Danger Form: Liquid Physical stat OSHA Hazards	 e: Liquid Color: Clear Odor: Sweet Flammable Liquid, Moderate skin irritant, Aspiration hazard, Specific target organ systemic toxicity - single exposure
Classification	: Flammable liquids, Category 2
SDS Number:100000067063	1/13

leptane Primary Ref	ference Fuel (PRF)
rsion 1.8	Revision Date 2016-01
	Skin irritation , Category 2 Specific target organ systemic toxicity - single exposure , Category 3 , Central nervous system Aspiration hazard , Category 1
Labeling	
Symbol(s)	
Signal Word	: Danger
Hazard Statements	 H225: Highly flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H336: May cause drowsiness or dizziness.
Precautionary Statements	 Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor/ physician if you feel unwell. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: P403 + P233 Store in a well-ventilated place. Keep cool. P403 + P235 Store in a well-ventilated place. Keep cool. P403 + P235 Store in a well-ventilated place. Keep cool. P403 + P235 Store in a well-ventilated place. Keep cool. P403 + P235 Itocked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.
Carcinogenicity:	
IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed
S Number:100000067063	2/13

leptane Primary Re	oforonce	Eucl (PRF)	SAFETY DATA SH
ion 1.8			Revision Date 2016-0
NTP	human carcinogen by IARC. No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.		
ACGIH	No ing	redient of this produte to 0.1% is identified	ict present at levels greater than or as a carcinogen or potential carcinoge
TION 3: Composition/info	rmation or	ingredients	
Synonyms		nal Heptane opilmetano	
Molecular formula	: C7H ²	16	
Component		CAS-No.	Weight %
n-Heptane		142-82-5	100
FION 4: First aid measure	s		
General advice	shee appe	t to the doctor in att	area. Show this material safety data endance. Symptoms of poisoning ma er. Do not leave the victim
If inhaled			onscious place in recovery position e. If symptoms persist, call a physiciar
In case of skin contact		n irritation persists, water. If on clothes	call a physician. If on skin, rinse well , remove clothes.
In case of eye contact	lense	es. Protect unharme	with plenty of water. Remove contac ed eye. Keep eye wide open while persists, consult a specialist.
If swallowed	give	milk or alcoholic bey th to an unconscious	ear. Do NOT induce vomiting. Do not verages. Never give anything by s person. Take victim immediately to
FION 5: Firefighting meas	ures		
		C (25 °F) iod: Tag closed cup	
Flash point			
		85 °C (398.93 °F)	
Flash point Autoignition temperature Suitable extinguishing media	: 203.		ioxide (CO2). Alcohol-resistant foam.
Autoignition temperature Suitable extinguishing	: 203. : Dry c		ioxide (CO2). Alcohol-resistant foam.

leptane Primary Re	fer	ence Fuel (PRF)
sion 1.8		Revision Date 2016-01
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	:	Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	Carbon oxides.
CTION 6: Accidental release	mea	asures
Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
CTION 7: Handling and stora	ige	
Handling		
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic

		SAFETY DATA SHEET
n-Heptane Primary Re	efer	ence Fuel (PRF)
Version 1.8		Revision Date 2016-01-21
		charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents".
Advice on protection against fire and explosion	:	Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Storage		
Requirements for storage areas and containers	:	No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

00				
Ingredients	Basis	Value	Control parameters	Note
n-Heptane	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	(b),
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	OSHA Z-1-A	STEL	500 ppm, 2,000 mg/m3	
	ACGIH	TWA	400 ppm,	
	ACGIH	STEL	500 ppm,	

(b) The value in mg/m3 is approximate.

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators
SDS Number:100000067063	5/13

	eference Fuel (PRF)
sion 1.8	Revision Date 2016-0
	may not provide adequate protection.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
TION 9: Physical and che	nical properties
Information on basic phy	sical and chemical properties
Appearance	
Form Physical state Color Odor	: Liquid : Liquid : Clear : Sweet
Safety data	
Flash point	: -4 °C (25 °F) Method: Tag closed cup
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7 %(V)
Oxidizing properties	: no
Autoignition temperature	: 203.85 °C (398.93 °F)
Molecular formula	: C7H16
Molecular weight	: 100.23 g/mol
рН	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 98 °C (208 °F)
Vapor pressure	: 1.60 PSI

	ference Fuel (PRF)
rsion 1.8	Revision Date 2016-01-
Relative density	: 0.69 at 16 °C (61 °F)
Density	: 5.75 L/G at 20 °C (68 °F)
Water solubility	: Negligible
Partition coefficient: n- octanol/water	: No data available
Relative vapor density	: 3.4 (Air = 1.0)
Evaporation rate	: 3.46
Percent volatile	: > 99 %
ner information	
Conductivity	: < 1 pSm at 20 °C
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous rea	actions
Conditions to avoid	: Not applicable.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Carbon oxides
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological info	ormation
Acute oral toxicity	
n-Heptane	 LD50: > 5,000 mg/kg Species: Rat Method: OECD Test Guideline 401 Information given is based on data obtained from similar substances.
n-Heptane Primary Referen	
Skin irritation	: Irritating to skin.
	: Irritating to skin. May cause skin irritation in susceptible persons.

n-Heptane Primary Reference Fuel (PRF)

Version 1.8

Revision Date 2016-01-21

Eye irritation	: Vapors may cause irritation to the eyes, respiratory system and the skin.
Sensitization	
n-Heptane	: Did not cause sensitization on laboratory animals. Information given is based on data obtained from similar substances.
Repeated dose toxicity	
n-Heptane	 Species: Rat, male Sex: male Application Route: Inhalation Dose: 12.47 mg/l Exposure time: 16 wk Number of exposures: 12 h/d, 7 d/wk NOEL: 12.47 mg/l No adverse effect has been observed in chronic toxicity tests
Reproductive toxicity	
n-Heptane	: Species: Rat Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 hr/d, 5 d/wk Test period: 13 wk Method: OECD Test Guideline 416 NOAEL Parent: 9000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm
Developmental Toxicity	
n-Heptane	: Species: Rat Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Exposure time: GD6-15 Number of exposures: 6 hrs/d NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm
n-Heptane Primary Refer Aspiration toxicity	 ence Fuel (PRF) May be fatal if swallowed and enters airways. Substances known to cause human aspiration toxicity hazard or to be regarded as if they cause human aspiration toxicity hazard.
CMR effects	
n-Heptane	 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: No toxicity to reproduction

leptane Primary Ro	eference Fuel (PRF)
ion 1.8	Revision Date 2016-0
n-Heptane Primary Refere Further information	 ence Fuel (PRF) Concentrations substantially above the TLV value may cause narcotic effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Solvents may degrease the skin.
TION 12: Ecological infor	mation
Toxicity to fish	
n-Heptane	 LL50: 1.284 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR
	LC50: 375 mg/l Exposure time: 96 h Species: Tilapia mosambica (Fish)
Toxicity to daphnia and o	other aquatic invertebrates
n-Heptane	: EC50: 1.5 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Toxic to aquatic organisms.
	LC50: 0.1 mg/l Exposure time: 96 h Species: Mysidopsis bahia (mysid shrimp) semi-static test Very toxic to aquatic organisms.
Toxicity to algae	
n-Heptane	 EL50: 4.338 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (microalgae) Method: QSAR
Biodegradability	
n-Heptane	: Result: Readily biodegradable. 70 % Testing period: 10 d
Ecotoxicology Assessme	ent
Acute aquatic toxicity n-Heptane	: Very toxic to aquatic life.
Chronic aquatic toxicity n-Heptane	: Very toxic to aquatic life with long lasting effects.
Number:100000067063	9/13

Heptane Primary Ref	SAFETY DATA SHE erence Fuel (PRF)
rsion 1.8	Revision Date 2016-01
Results of PBT assessment	
n-Heptane	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.
CTION 13: Disposal considera	ations
The information in this SDS p	ertains only to the product as shipped.
may meet the criteria of a haz other State and local regulation regulated components may be	burpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for e necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste
Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
CTION 14: Transport informat	tion
	shown here are for bulk shipments only, and may not apply to ages (see regulatory definition).
Goods Regulations for additionetc.) Therefore, the information	estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or name on shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and t
	DEPARTMENT OF TRANSPORTATION) I, MARINE POLLUTANT, (HEPTANES)
	AL MARITIME DANGEROUS GOODS) I, (-4 °C), MARINE POLLUTANT, (HEPTANES)
IATA (INTERNATIONAL AIR UN1206, HEPTANES, 3, I	TRANSPORT ASSOCIATION)
	NGEROUS GOODS BY ROAD (EUROPE)) I, (D/E), ENVIRONMENTALLY HAZARDOUS, (HEPTANES)
	ERNING THE INTERNATIONAL TRANSPORT OF
DANGEROUS GOODS (EUR UN1206, HEPTANES, 3, II,	, ENVIRONMENTALLY HAZARDOUS, (HEPTANES)

n-Heptane Primary Reference Fuel (PRF)

Version 1.8

Revision Date 2016-01-21

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS) UN1206, HEPTANES, 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANES)					
ransport in bulk according to Annex II of MARPOL 73/78 and the IBC Code					
SECTION 15: Regulatory informa National legislation	tion				
SARA 311/312 Hazards	: Fire Hazard Acute Health Hazard				
EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO – KNOW					
CERCLA Reportable Quantity	: This material does not contain any components with a CERCLA RQ.				
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.				
SARA 302 Threshold Planning Quantity	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.				
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.				
SARA 313 Ingredients	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.				
Clean Air Act					
Ozone-Depletion : This product neither contains, nor was manufactured with a Class I or Potential Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).					
This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).					
SDS Number:100000067063	11/13				

n-Heptane Primary Reference Fuel (PRF)

Version 1.8

Revision Date 2016-01-21

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know

: n-Heptane - 142-82-5 New Jersey Right To Know : n-Heptane - 142-82-5

California Prop. 65 : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America TSCA	:	On the inventory, or in compliance with the inventory
Canada DSL	:	On the inventory, or in compliance with the inventory
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification
: Health Hazard: 1
Fire Hazard: 3
Reactivity Hazard: 0

Further information
Legacy SDS Number
: 26960

n-Heptane Primary Reference Fuel (PRF)

Version 1.8

Revision Date 2016-01-21

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Ke	y or legend to abbreviations and a	cronyms used	in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		